

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Toluene, 250 ml**

Print date: 15.04.2015

Product code: 9991955

Page 1 of 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Toluene, 250 ml

CAS No: 108-88-3  
Index No: 601-021-00-3  
EC No: 203-625-9

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Laboratory chemicals

**1.3. Details of the supplier of the safety data sheet****Seller**

Company name: CONATEX-DIDACTIC Lehrmittel GmbH  
Street: Im Forstgarten 1  
Place: D-66459 Kirkel  
Internet: www.conatex.com

**Supplier**

Company name: Carbolution Chemicals GmbH  
Street: Im Stadtwald, Gebäude A1.2  
Place: D-66123 Saarbrücken  
Contact person: Dr. Michael Bauer Telephone: +49 (0)681 302-71232  
e-mail: michael.bauer@carbolution-chemicals.de  
Internet: www.carbolution-chemicals.de

**1.4. Emergency telephone number:** +49 (0)681 302-71232**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Directive 67/548/EEC or 1999/45/EC**

Indications of danger: F - Highly flammable, R3 - Repr. Cat. 3, Xn - Harmful, Xi - Irritant

R phrases:

Highly flammable.

Possible risk of harm to the unborn child.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful: may cause lung damage if swallowed.

Irritating to skin.

Vapours may cause drowsiness and dizziness.

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Reproductive toxicity: Repr. 2

Aspiration hazard: Asp. Tox. 1

Specific target organ toxicity - repeated exposure: STOT RE 2

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Suspected of damaging the unborn child.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene, 250 ml

Print date: 15.04.2015

Product code: 9991955

Page 2 of 8

May be fatal if swallowed and enters airways.  
 May cause damage to organs through prolonged or repeated exposure.  
 Causes skin irritation.  
 May cause drowsiness or dizziness.

#### 2.2. Label elements

##### Hazardous components which must be listed on the label

toluene

Signal word:

Danger

Pictograms:

GHS02-GHS07-GHS08



##### Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

##### Precautionary statements

P280	Wear protective gloves/protective clothing/eye protection/face protection.
------	--

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Sum formula:	C <sub>7</sub> H <sub>8</sub>
Molecular weight:	92,14

##### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
203-625-9	toluene	100 %
108-88-3	Repr. Cat. 3, F - Highly flammable, Xn - Harmful, Xi - Irritant R11-63-48/20-65-38-67	
601-021-00-3	Flam. Liq. 2, Repr. 2, Asp. Tox. 1, STOT RE 2, Skin Irrit. 2, STOT SE 3; H225 H361d *** H304 H373 ** H315 H336	

Full text of R-, H- and EUH-phrases: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

##### After inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

##### After contact with skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene, 250 ml

Print date: 15.04.2015

Product code: 9991955

Page 3 of 8

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Rinse mouth immediately and drink plenty of water.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

No data available

### SECTION 5: Firefighting measures

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>). Foam. Extinguishing powder.

#### **5.2. Special hazards arising from the substance or mixture**

Combustible. Vapours may form explosive mixtures with air.

#### **5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. Full protective suit.

#### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

#### **6.2. Environmental precautions**

Do not allow uncontrolled discharge of product into the environment. Explosion hazard.

#### **6.3. Methods and material for containment and cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### SECTION 7: Handling and storage

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition. - No smoking.

##### **Advice on storage compatibility**

Do not store together with: Material, rich in oxygen, oxidizing.

### SECTION 8: Exposure controls/personal protection

#### **8.1. Control parameters**

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Toluene, 250 ml

Print date: 15.04.2015

Product code: 9991955

Page 4 of 8

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL

### 8.2. Exposure controls

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

#### Eye/face protection

Eye protection: Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

#### Hand protection

Hand protection: Single-use gloves. Before using check leak tightness / impermeability. Use gloves only once. German Industry Norms (DIN) / European Norms (EN): DIN EN 374

#### Skin protection

Body protection: Lab apron. Only wear fitting, comfortable and clean protective clothing.

#### Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protective equipment: particulates filter device (DIN EN 143).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	colourless
Odour:	No data available

#### Test method

pH-Value:	No data available
-----------	-------------------

#### Changes in the physical state

Initial boiling point and boiling range:	110 °C
Sublimation point:	No data available
Softening point:	No data available
Flash point:	4 °C

#### Flammability

Solid:	No data available
Gas:	No data available

Lower explosion limits:	1,2 vol. %
Upper explosion limits:	7 vol. %
Ignition temperature:	No data available

#### Auto-ignition temperature

Solid:	No data available
Gas:	535 °C

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene, 250 ml

Print date: 15.04.2015

Product code: 9991955

Page 5 of 8

Vapour pressure: (at 20 °C)	29,1 hPa
Vapour pressure:	No data available
Density:	No data available
Water solubility:	No data available
Partition coefficient:	No data available
Viscosity / dynamic:	No data available
Viscosity / kinematic:	No data available
Flow time:	No data available
Vapour density:	No data available
Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available

#### **9.2. Other information**

Solid content:	No data available
----------------	-------------------

### SECTION 10: Stability and reactivity

#### **10.1. Reactivity**

No data available

#### **10.3. Possibility of hazardous reactions**

No data available

#### **10.4. Conditions to avoid**

Keep away from heat. Ignition hazard.

#### **10.5. Incompatible materials**

Oxidizing agents, strong.

#### **10.6. Hazardous decomposition products**

In case of fire may be liberated: Carbon monoxide. Carbon dioxide.

### SECTION 11: Toxicological information

#### **11.1. Information on toxicological effects**

##### **Toxicokinetics, metabolism and distribution**

Toxicological data are not available.

##### **Acute toxicity**

Acute toxicity, inhalant.

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
108-88-3	toluene				
	dermal	LD50	12200 mg/kg	Kaninchen	
	inhalative (4 h) vapour	LC50	49 mg/l	Ratte	

##### **Irritation and corrosivity**

Vapours may cause drowsiness and dizziness. After skin contact: Irritant.

##### **Sensitising effects**

No data available

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Toluene, 250 ml

Print date: 15.04.2015

Product code: 9991955

Page 6 of 8

### Severe effects after repeated or prolonged exposure

Danger of serious damage to health by prolonged exposure.

### Carcinogenic/mutagenic/toxic effects for reproduction

May damage the unborn child.

### Specific effects in experiment on an animal

No data available

### Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

### Practical experience

### Observations relevant to classification

No data available

## SECTION 12: Ecological information

### 12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
108-88-3	toluene					
	Acute fish toxicity	LC50	13 mg/l	96 h	Carassius auratus	
	Acute algae toxicity	ErC50	12,5 mg/l	72 h	Algen	

### 12.2. Persistence and degradability

No data available

### 12.3. Bioaccumulative potential

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.6. Other adverse effects

No data available

### Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

Dispose of waste according to applicable legislation.

#### Waste disposal number of waste from residues/unused products

- 160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing dangerous substances, including mixtures of laboratory chemicals  
Classified as hazardous waste.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Toluene, 250 ml

Print date: 15.04.2015

Product code: 9991955

Page 7 of 8

### Waste disposal number of used product

160506 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; laboratory chemicals, consisting of or containing dangerous substances, including mixtures of laboratory chemicals  
Classified as hazardous waste.

### Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances  
Classified as hazardous waste.

### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number:** UN1294  
**14.2. UN proper shipping name:** TOLUENE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3  
Classification code: F1  
Limited quantity: 1 L  
Transport category: 2  
Hazard No: 33  
Tunnel restriction code: D/E

### Other applicable information (land transport)

E2

### Inland waterways transport (ADN)

**14.1. UN number:** UN1294  
**14.2. UN proper shipping name:** TOLUENE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3  
Classification code: F1  
Limited quantity: 1 L

### Other applicable information (inland waterways transport)

E2

### Marine transport (IMDG)

**14.1. UN number:** UN1294  
**14.2. UN proper shipping name:** TOLUENE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3  
Special Provisions: -  
Limited quantity: 1 L  
EmS: F-E, S-D

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Toluene, 250 ml

Print date: 15.04.2015

Product code: 9991955

Page 8 of 8

#### Other applicable information (marine transport)

E2

#### Air transport (ICAO)

**14.1. UN number:** UN1294

**14.2. UN proper shipping name:** TOLUENE

**14.3. Transport hazard class(es):** 3

**14.4. Packing group:** II

Hazard label: 3

Limited quantity Passenger: 1 L

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

#### Other applicable information (air transport)

E2

: Y341

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

2004/42/EC (VOC): 100 %

##### Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

##### National regulatory information

Water contaminating class (D): 2 - water contaminating

### SECTION 16: Other information

#### Relevant R-phrases (Number and full text)

- 11 Highly flammable.
- 38 Irritating to skin.
- 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 63 Possible risk of harm to the unborn child.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.

#### Relevant H- and EUH-phrases (Number and full text)

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs (...) through prolonged or repeated exposure (inhalation, ingestion).
- H373 May cause damage to organs through prolonged or repeated exposure.